

Features







Strong magnet



Audio monitor



Automatic power saving



IP65 industrial design



Automatic storage if no network

Functions



Overspeed Alert

Support



Geo-fence Alert

Support



Vibration Alert Support





Mutiple Working Mode Support



Remote Setting SMS,WEB,APP

Specifications



6000 mAh Battery capacity



3.6-4.2 V Working voltage



50 mA Working current



5 mA Standby current

166.7 g



96 Hours Run-time









	3% [0 95%
	Working	g humidity
_		

Dimension	80 x 50 x 35 mm
DILIGINSION	00 X 30 X 33 IIIIII

Parameters

Weight

Positioning System	GPS + BDS
GPS Frequency	L1
GPS Sensitivity	-160 dBm
Acquisition Sensitivity	-144 dBm
Location Accuracy	< 5 m
GPS Antenna	Ceramic Antenna

Communication band	Quad-band: 850/900/1800/1900 MHz FDD-LTE: B1/2/3/4/5/7/8/20/28/66 TDD-LTE: B34/38/39/40/41
Cellular Connectivity	GSM / LTE Cat.1
TTFF Open Sky	Cold Start ≤ 45s, Hot Start ≤ 10s
LED Indicator	Blue-GNSS, Green-Cellular, Red-Power
Cellular Antenna	FPC Antenna

Scenes







Car Rent

Personal Tracking

Logistics Track